

# Basic Functionality at the Highest Level

PRObas Power Supply – High-efficiency, Reliable and Affordable



**Weidmüller** 



## Robust and Reliable PRObas Power Supply

### Optimal combination of all basic functions in a compact design

A safe and stable DC supply voltage is at the heart of many automation applications. The single-phase switched-mode power supply units of the PRObas series meet the high requirements of mechanical engineering in a cost-effective way. The know-how of the successful PROeco, PROmax and PROtop series flows into this attractive product series.

High performance, compact design and a good price-performance ratio are the main characteristics of the new PRObas power supplies. The product family comprises 12 variants with 5, 12, 24 or 48 V DC output voltage and a wide-range input. All units have comprehensive safety functions and are internationally approved. Due to compatibility with our electronic fuses, DC UPS and diode modules, they are also suitable for setting up power management systems.

### Industries and Applications

The single phase power supply is the heart of the automation machines which are requiring the stable and safe DC control voltage. The new series of power supply PRObas fit optimally in machine construction applications where space, efficiency and cost effectiveness are the top priorities.

#### Machine & Factory Automation

- Consumer Goods & Packaging
- Elevators & Escalators
- Intralogistics

#### Energy

- Photovoltaics
- Traditional Power

#### Process

- Water Treatment

#### Building Infrastructure

- Office Buildings
- Industrial Buildings
- Commercial Buildings





# PRObas Power Supply

## Ordering Data

Type	Description	Order Number
PRO BAS 30W 24V 1.3A	Switch-mode power supply unit, 24 V, 1.3A, Class 2 Power	2838500000
PRO BAS 30W 12V 2.6A	Switch-mode power supply unit, 12 V, 2.6A, Class 2 Power	2838510000
PRO BAS 30W 5V 6A	Switch-mode power supply unit, 5 V, 6A, Class 2 Power	2838400000
PRO BAS 60W 24V 2.5A	Switch-mode power supply unit, 24 V, 2.5A, Class 2 Power	2838410000
PRO BAS 60W 12V 5A	Switch-mode power supply unit, 12 V, 5A, Class 2 Power	2838420000
PRO BAS 90W 24V 3.8A	Switch-mode power supply unit, 24 V, 3.8A, Class 2 Power	2838430000
PRO BAS 120W 24V 5A	Switch-mode power supply unit, 24 V, 5A	2838440000
PRO BAS 120W 12V 10A	Switch-mode power supply unit, 12 V, 10A	2838450000
PRO BAS 240W 24V 10A	Switch-mode power supply unit, 24 V, 10A	2838460000
PRO BAS 240W 48V 5A	Switch-mode power supply unit, 48 V, 5A	2838470000
PRO BAS 480W 24V 20A	Switch-mode power supply unit, 24 V, 20A	2838480000
PRO BAS 480W 48V 10A	Switch-mode power supply unit, 48 V, 10A	2838490000

## Features & Benefits

- Robust and reliable
- Operates in a wide temperature range from  $-25^{\circ}\text{C}$ – $70^{\circ}\text{C}$
- Flexible mounting, either on mounting rails or directly screwed to the cabinet wall
- High MTBF value
- Extremely compact and energy-efficient
- High-cost efficiency, strong performance and compact design
- Universal use due to a wide range of variants and international approvals (e.g. cULus, NEC Class 2 and cCSAus)

## Approvals



**NEC CLASS 2** for units up to 90W

# Technical Data



	PRO BAS 30W 5 V / 6 A 2838400000	PRO BAS 30W 12 V / 2.6 A 2838510000	PRO BAS 30W 24 V / 1.3 A 2838500000
<b>Input Data</b>			
Nominal input voltage, AC / DC	100...240 V AC / 120...340 V DC	100...240 V AC / 120...340 V DC	100...240 V AC / 120...340 V DC
Input voltage range, AC / DC (derating -1%/V @ < 100 V AC, < 120 V DC)	85...264 V AC / 110...370 V DC	85...264 V AC / 110...370 V DC	85...264 V AC / 110...370 V DC
Frequency range, AC	45...65 Hz	45...65 Hz	45...65 Hz
Input current typ., AC / DC	0.34 A @ 230 V AC, 0.56 A @ 115 V AC, 0.28 A @ 120 V DC	0.33 A @ 230 V AC, 0.56 A @ 115 V AC, 0.29 A @ 120 V DC	0.33 A @ 230 V AC, 0.55 A @ 115 V AC, 0.29 A @ 120 V DC
Max. start-up current	40 A @ 230 V AC, 25°C	40 A @ 230 V AC, 25°C	40 A @ 230 V AC, 25°C
Input fuse (internal)	yes	yes	yes
Recommended back-up fuse 1), Safety cut-out fuse / Miniature circuit breaker	2 A / 6 A, 2...4 A	2 A / 6 A, 2...4 A	2 A / 6 A, 2...4 A
<b>Output Data</b>			
Nominal output voltage (adjustable via potentiometer)	5 V DC (3...8 V DC)	12 V DC (9...16 V DC)	24 V DC (22...28 V DC)
Residual ripple, switching peaks (20 MHz)	≤ 50 mV <sub>pp</sub> @ full load	≤ 50 mV <sub>pp</sub> @ full load	≤ 50 mV <sub>pp</sub> @ full load
Nominal output current @ Unom	6 A @ 55 °C	2.6 A @ 55 °C	1.3 A @ 55 °C
Continuous output current @ Unom (2.5 %/K derating above 55 °C)	6 A @ 55 °C, 3.75 A @ 70 °C	2.6 A @ 55 °C, 1.625 A @ 70 °C	1.3 A @ 55 °C, 0.812 A @ 70 °C
Output characteristic curve / current limit	I <sub>U</sub> , I <sub>Limit</sub> : 110 - 130 %	I <sub>U</sub> , I <sub>Limit</sub> : 110 - 130 %	I <sub>U</sub> , I <sub>Limit</sub> : 110 - 130 %
Start-up period, max.	< 300 ms	< 300 ms	< 300 ms
Capacitive load	unlimited	unlimited	unlimited
<b>Status Indicator</b>			
DC OK: LED green	$U_{out} > 0.9 U_{nom\_min}$	$U_{out} > 0.9 U_{nom\_min}$	$U_{out} > 0.9 U_{nom\_min}$
<b>Environmental Conditions</b>			
Ambient temperature, operational / storage, transport	-25...+70 °C / -40...+85 °C	-25...+70 °C / -40...+85 °C	-25...+70 °C / -40...+85 °C
Max. permitted humidity (operational)	5 %...95 % RH	5 %...95 % RH	5 %...95 % RH
<b>General Data</b>			
Power dissipation typ. @ 230 V AC, no-load / rated load	0.3 W / 4.5 W	0.3 W / 4.3 W	0.3 W / 3.9 W
Efficiency degree, typ. @ 230 V AC	86 %	88 %	89 %
Power factor, typ.	0.54 @ 120 V AC, 0.45 @ 230 V AC	0.54 @ 120 V AC, 0.47 @ 230 V AC	0.54 @ 120 V AC, 0.47 @ 230 V AC
Mains failure bridging @ I <sub>nom</sub>	> 20ms @ 120V AC, > 80ms @ 230V AC	> 20ms @ 120V AC, > 80ms @ 230V AC	> 20ms @ 120V AC, > 80ms @ 230V AC
Protection class	IP20	IP20	IP20
Protection class	II	II	II
Pollution degree	2	2	2
Insulation voltage, input-output	3.5 kV AC, 1 min.	3.5 kV AC, 1 min.	3.5 kV AC, 1 min.
Earth discharge current	< 3.5 mA	< 3.5 mA	< 3.5 mA
MTBF acc. to IEC 61709 (SN29500) @ 40°C	> 1200000 h	> 950000 h	> 950000 h
Short-circuit protection	yes	yes	yes
Protection against inverse voltages from the load	< 9 V DC	< 18 V DC	< 35 V DC
Parallel capability	yes	yes	yes
Plastic housing	yes	yes	yes
Dimensions (Height x Width x Depth) in mm	90 x 36 x 85 mm	90 x 23 x 85 mm	90 x 23 x 85 mm
Weight	245 g	163 g	162 g
Approvals / Markings / Standards / Directives	CE, cULus, cCSAus, NEC Class 2	CE, cULus, cCSAus, NEC Class 2	CE, cULus, cCSAus, NEC Class 2
<b>Connection Data, Input / Output</b>			
Number of terminals, input / output	2 (L+, N-) / 4 (+, -, -, -)	2 (L+, N-) / 3 (+, -, -)	2 (L+, N-) / 3 (+, -, -)
Rigid wire cross-section	0.2 ...6 mm <sup>2</sup>	0.2 ...6 mm <sup>2</sup>	0.2 ...6 mm <sup>2</sup>
Flexible wire cross-section	0.5 2.5 mm <sup>2</sup>	0.5 2.5 mm <sup>2</sup>	0.5 2.5 mm <sup>2</sup>
Wire cross-section AWG	26...12	26...12	26...12
Insulation stripping length	6 mm	6 mm	6 mm
Torque, min. / max.	0.5 Nm / 0.6 Nm	0.5 Nm / 0.6 Nm	0.5 Nm / 0.6 Nm
Screwdriver blade	0.6 x 3.5 mm	0.6 x 3.5 mm	0.6 x 3.5 mm
<b>EMC / shock / vibration</b>			
Interference radiation acc. to EN 55032 (Class)	B	B	B
Shock resistance (in all directions) acc. to IEC 60068-2-27 / Vibration resistance acc. to IEC 60068-2-6	30 g / 0.7 g	30 g / 0.7 g	30 g / 0.7 g
<b>Electrical Safety</b>			
Extra-low safety voltage according to	SELV: IEC 61010-1, PELV: IEC 61010-2-201		
Note: For AC operation, the max. permissible operating voltage must be observed in any case.			

# Technical Data



	<b>PRO BAS 60W 12V 5A 2838420000</b>	<b>PRO BAS 60W 24V 2.5A 2838410000</b>	<b>PRO BAS 90W 24V 3.8A 2838430000</b>
<b>Input Data</b>			
Nominal input voltage, AC / DC	100...240 V AC / 120...340 V DC	100...240 V AC / 120...340 V DC	100...240 V AC / 120...340 V DC
Input voltage range, AC / DC (derating -1%/V @ < 100 V AC, < 120 V DC)	85...264 V AC / 110...370 V DC	85...264 V AC / 110...370 V DC	85...264 V AC / 110...370 V DC
Frequency range, AC	45...65 Hz	45...65 Hz	45...65 Hz
Input current typ., AC / DC	0.62 A @ 230 V AC, 1.04 A @ 115 V AC, 0.55 A @ 120 V DC	0.61 A @ 230 V AC, 1.01 A @ 115 V AC, 0.54 A @ 120 V DC	0.89 A @ 230 V AC, 1.54 A @ 115 V AC, 0.83 A @ 120 V DC
Max. start-up current	40 A @ 230 V AC, 25°C	40 A @ 230 V AC, 25°C	40 A @ 230 V AC, 25 °C
Input fuse (internal)	yes	yes	yes
Recommended back-up fuse 1), Safety cut-out fuse / Miniature circuit breaker	2 A / 6 A, 2...4 A	2 A / 6 A, 2...4 A	4 A / 6 A, 2...4 A
<b>Output Data</b>			
Nominal output voltage (adjustable via po- tentiometer)	12 V DC (9...16 V DC)	24 V DC (22...28 V DC)	24 V DC (22...25 V DC)
Residual ripple, switching peaks (20 MHz)	≤ 50 mV <sub>pp</sub> @ full load	≤ 50 mV <sub>pp</sub> @ full load	≤ 50 mV <sub>pp</sub> @ full load
Nominal output current @ Unom	5 A @ 55 °C	2.5 A @ 55 °C	3.8 A @ 55 °C
Continuous output current @ Unom (2.5 %/K derating above 55 °C)	5 A @ 55 °C, 3.125 A @ 70 °C	2.5 A @ 55 °C, 1.65 A @ 70 °C	3.8 A @ 55 °C, 2.375 A @ 70 °C
Output characteristic curve / current limit	IU, ILimit: 110 - 130 %	IU, ILimit: 110 - 130 %	IU, ILimit: 105 - 110 %
Start-up period, max.	< 300 ms	< 300 ms	< 300 ms
Capacitive load	unlimited	unlimited	unlimited
<b>Status Indicator</b>			
DC OK: LED green	$U_{out} > 0.9 U_{nom\_min}$	$U_{out} > 0.9 U_{nom\_min}$	$U_{out} > 0.9 U_{nom\_min}$
<b>Environmental Conditions</b>			
Ambient temperature, operational / storage, transport	-25...+70 °C / -40...+85 °C	-25...+70 °C / -40...+85 °C	-25...+70 °C / -40...+85 °C
Max. permitted humidity (operational)	5 %...95 % RH	5 %...95 % RH	5 %...95 % RH
<b>General Data</b>			
Power dissipation typ. @ 230 V AC, no- load / rated load	0.3 W / 6.5 W	0.3 W / 6.6 W	0.3 W / 10.8 W
Efficiency degree, typ. @ 230 V AC	90 %	90 %	89 %
Power factor, typ.	0.56 @ 120 V AC, 0.47 @ 230 V AC	0.56 @ 120 V AC, 0.47 @ 230 V AC	0.58 @ 120 V AC, 0.49 @ 230 V AC
Mains failure bridging @ I <sub>nom</sub>	> 20ms @ 120V AC, > 80ms @ 230V AC	> 20ms @ 120V AC, > 80ms @ 230V AC	> 20ms @ 120 VAC, > 80ms @ 230V AC
Protection class	IP20	IP20	IP20
Protection class	II	II	II
Pollution degree	2	2	2
Insulation voltage, input-output	3.5 kV AC, 1 min.	3.5 kV AC, 1 min.	3.5 kV AC, 1 min.
Earth discharge current	< 3.5 mA	< 3.5 mA	< 3.5 mA
MTBF acc. to IEC 61709 (SN29500) @ 40°C	> 850000 h	> 750000 h	> 750000 h
Short-circuit protection	yes	yes	yes
Protection against inverse voltages from the load	< 18 V DC	< 35 V DC	< 35 V DC
Parallel capability	yes	yes	yes
Plastic housing	yes	yes	yes
Dimensions (Height x Width x Depth) in mm	90 x 36 x 85 mm	90 x 36 x 85 mm	90 x 47 x 85 mm
Weight	259 g	258 g	376 g
Approvals / Markings / Standards / Directives	CE, cULus, cCSAus, NEC Class 2	CE, cULus, cCSAus, NEC Class 2	CE, cULus, cCSAus, NEC Class 2
<b>Connection Data, Input / Output</b>			
Number of terminals, input / output	2 (L+, N-) / 4 (+, +, -, -)	2 (L+, N-) / 4 (+, +, -, -)	2 (L+, N-) / 4 (+, +, -, -)
Rigid wire cross-section	0.2 ...6 mm <sup>2</sup>	0.2 ...6 mm <sup>2</sup>	0.2 ...6 mm <sup>2</sup>
Flexible wire cross-section	0.5 2.5 mm <sup>2</sup>	0.5 2.5 mm <sup>2</sup>	0.5 2.5 mm <sup>2</sup>
Wire cross-section AWG	26...12	26...12	26...12
Insulation stripping length	6 mm	6 mm	6 mm
Torque, min. / max.	0.5 Nm / 0.6 Nm	0.5 Nm / 0.6 Nm	0.5 Nm / 0.6 Nm
Screwdriver blade	0.6 x 3.5 mm	0.6 x 3.5 mm	0.6 x 3.5 mm
<b>EMC / shock / vibration</b>			
Interference radiation acc. to EN 55032 (Class)	B	B	B
Shock resistance (in all directions) acc. to IEC 60068-2-27 / Vibration resistance acc. to IEC 60068-2-6	30 g / 0.7 g	30 g / 0.7 g	30 g / 0.7 g
<b>Electrical Safety</b>			
Extra-low safety voltage according to	SELV: IEC 61010-1, PELV: IEC 61010-2:201		
Note: For AC operation, the max. permissible operating voltage must be observed in any case.			

# Technical Data



	PRO BAS 120W 12V 10A 2838450000	PRO BAS 120W 24V 5A 2838440000	PRO BAS 240W 24V 10A 2838460000
<b>Input Data</b>			
Nominal input voltage, AC / DC	100...240 V AC / 120...340 V DC	100...240 V AC / 120...340 V DC	100...240 V AC / 120...340 V DC
Input voltage range, AC / DC (derating -1%/V @ < 100 V AC, < 120 V DC)	85...264 V AC / 110...370 V DC	85...264 V AC / 110...370 V DC	85...264 V AC / 110...370 V DC
Frequency range, AC	45...65 Hz	45...65 Hz	45...65 Hz
Input current typ., AC / DC	1.14 A @ 230 V AC, 2.04 A @ 115 V AC, 1.12 A @ 120 V DC	1.134 A @ 230 V AC, 2.02 A @ 115 V AC, 1.11 A @ 120 V DC	1.135 A @ 230 V AC, 2.30 A @ 115 V AC, 2.22 A @ 120 V DC
Max. start-up current	40 A @ 230 V AC, 25 °C	40 A @ 230 V AC, 25 °C	20 A @ 230 V AC, 25 °C
Input fuse (internal)	yes	yes	yes
Recommended back-up fuse 1), Safety cut-out fuse / Miniature circuit breaker	4 A / 6 A, 3...5 A	4 A / 6 A, 3...5 A	4 A / 6 A, 3...5 A
<b>Output Data</b>			
Nominal output voltage (adjustable via po- tentiometer)	12 V DC (9...12 V DC)	24 V DC (22...28 V DC)	24 V DC (22...28 V DC)
Residual ripple, switching peaks (20 MHz)	≤ 50 mV <sub>pp</sub> @ full load	≤ 50 mV <sub>pp</sub> @ full load	≤ 100 mV <sub>pp</sub> @ full load
Nominal output current @ Unom	10 A @ 55 °C	5 A @ 55 °C	10 A @ 55 °C
Continuous output current @ Unom (2.5 %/K derating above 55 °C)	10 A @ 55 °C, 6.25 A @ 70 °C	5 A @ 55 °C, 3.125 A @ 70 °C	10 A @ 55 °C, 6.25 A @ 70 °C
Output characteristic curve / current limit	I <sub>U</sub> , I <sub>Limit</sub> : 110 - 130 %	I <sub>U</sub> , I <sub>Limit</sub> : 110 - 130 %	Hiccup, I <sub>Limit</sub> : 110 - 130 %
Start-up period, max.	< 400 ms	< 400 ms	< 400 ms
Capacitive load	unlimited	unlimited	5500 µF
<b>Status Indicator/ Status Relay</b>			
DC OK: LED green , Relay: ON	> 0.9 U <sub>out</sub>	> 0.9 U <sub>out</sub>	> 0.9 U <sub>out</sub>
Max. contact switching power	30 V AC / DC, 1 A	30 V AC / DC, 1 A	30 V AC / DC, 1 A
Contact type	N. O. (SPST)	N. O. (SPST)	N. O. (SPST)
<b>Environmental Conditions</b>			
Ambient temperature, operational / storage, transport	-25...+70 °C / -40...+85 °C	-25...+70 °C / -40...+85 °C	-25...+70 °C / -40...+85 °C
Max. permitted humidity (operational)	5 %...95 % RH	5 %...95 % RH	5 %...95 % RH
<b>General Data</b>			
Power dissipation typ. @ 230 V AC, no-load / rated load	1.2 W / 15.4 W	1.5 W / 14.5 W	2 W / 19.5 W
Efficiency degree, typ. @ 230 V AC	90 %	90 %	94 %
Power factor, typ.	0.58 @ 120 V AC, 0.5 @ 230 V AC	0.58 @ 120 V AC, 0.5 @ 230 V AC	0.98 @ 120 V AC full load, 0.96 @ 230 V AC full load
Mains failure bridging @ I <sub>nom</sub>	> 20ms @ 120V AC, > 60ms @ 230V AC	> 20ms @ 120V AC, > 60ms @ 230V AC	> 25ms @ 120V AC, > 25ms @ 230V AC
Protection class	IP20	IP20	IP20
Protection class	I	I	I
Pollution degree	2	2	2
Insulation voltage, input-output	3.5 kV AC / 3.0 kV AC / 0.5 kV AC, 1 min.	3.5 kV AC / 3.0 kV AC / 0.5 kV AC, 1 min.	3.5 kV AC / 3.0 kV AC / 0.5 kV AC, 1 min.
Earth discharge current	< 3.5 mA	< 3.5 mA	< 3.5 mA
MTBF acc. to IEC 61709 (SN29500) @ 40°C	> 600000 h	> 600000 h	> 590000 h
Short-circuit protection	yes	yes	yes
Protection against inverse voltages from the load	< 18 V DC	< 35 V DC	< 35 V DC
Parallel capability	yes	yes	yes
Plastic housing	yes	yes	yes
Dimensions (Height x Width x Depth) in mm	130 x 40 x 100 mm	130 x 40 x 100 mm	130 x 52 x 100 mm
Weight	488 g	490 g	629 g
Approvals / Markings / Standards / Directives	CE, cULus, cCSAus	CE, cULus, cCSAus	CE, cULus, cCSAus
<b>Connection Data, Input / Output</b>			
Number of terminals, input / output/ N. O. relay (PUSH IN)	3 (L+, N-, PE) / 4 (+, +, -, -) / 2 (13,14)	3 (L+, N-, PE) / 4 (+, +, -, -) / 2 (13,14)	3 (L+, N-, PE) / 4 (+, +, -, -) / 2 (13,14)
Rigid wire cross-section	0.2...6mm <sup>2</sup> / 0.2...6mm <sup>2</sup> / 0.2...1.5mm <sup>2</sup>	0.2...6mm <sup>2</sup> / 0.2...6mm <sup>2</sup> / 0.2...1.5mm <sup>2</sup>	0.2...6 mm <sup>2</sup> / 0.2...6 mm <sup>2</sup> / 0.2...1.5 mm <sup>2</sup>
Flexible wire cross-section	0.5...2.5mm <sup>2</sup> / 0.5...2.5mm <sup>2</sup> / 0.5...0.75mm <sup>2</sup>	0.5...2.5mm <sup>2</sup> / 0.5...2.5mm <sup>2</sup> / 0.5...0.75mm <sup>2</sup>	0.5...2.5mm <sup>2</sup> / 0.5...2.5mm <sup>2</sup> / 0.2...0.75mm <sup>2</sup>
Wire cross-section AWG	26...12 / 26...12 / 28...14	26...12 / 26...12 / 28...14	26...12 / 26...12 / 28...14
Insulation stripping length	6 mm / 6 mm / 10 mm	6 mm / 6 mm / 10 mm	6 mm / 6 mm / 10 mm
Torque, min. / max.	0.5 Nm / 0.6 Nm	0.5 Nm / 0.6 Nm	0.5 Nm / 0.6 Nm
Screwdriver blade	0.6 x 3.5 mm	0.6 x 3.5 mm	0.6 x 3.5 mm
<b>EMC / shock / vibration</b>			
Interference radiation acc. to EN 55032 (Class)	B	B	B
Shock resistance (in all directions) acc. to IEC 60068-2-27 / Vibration resistance acc. to IEC 60068-2-6	30 g / 0.7 g	30 g / 0.7 g	30 g / 0.7 g
<b>Electrical Safety</b>			
Extra-low safety voltage according to	SELV: IEC 61010-1, PELV: IEC 61010-2-201		
Note: For AC operation, the max. permissible operating voltage must be observed in any case.			

# Technical Data



	PRO BAS 240W 48V 5A 2838470000	PRO BAS 480W 24V 20A 2838480000	PRO BAS 480W 48V 10A 2838490000
<b>Input Data</b>			
Nominal input voltage, AC / DC	100...240 V AC / 120...340 V DC	100...240 V AC / 120...340 V DC	100...240 V AC / 120...340 V DC
Input voltage range, AC / DC (derating -1%/V @ < 100 V AC, < 120 V DC)	85...264 V AC / 110...370 V DC	85...264 V AC / 110...370 V DC	85...264 V AC / 110...370 V DC
Frequency range, AC	45...65 Hz	45...65 Hz	45...65 Hz
Input current typ., AC / DC	1.129 A @ 230 V AC, 2.287 A @ 115 V AC, 2.296 A @ 120 V DC	2.26 A @ 230 V AC, 4.584 A @ 115 V AC, 4.42 A @ 120 V DC	2.23 A @ 230 V AC, 4.576 A @ 115 V AC, 4.39 A @ 120 V DC
Max. start-up current	20 A @ 230 V AC, 25 °C	20 A @ 230 V AC, 25 °C	20 A @ 230 V AC, 25 °C
Input fuse (internal)	yes	yes	yes
Recommended back-up fuse 1), Safety cut-out fuse / Miniature circuit breaker	4 A / 6 A, 3...5 A	6 A / 16 A, 6...8 A	6 A / 16 A, 6...8 A
<b>Output Data</b>			
Nominal output voltage (adjustable via potentiometer)	48 V DC (36...56 V DC)	24 V DC (22...28 V DC)	48 V DC (36...56 V DC)
Residual ripple, switching peaks (20 MHz)	≤ 100 mV <sub>pp</sub> @ full load	≤ 100 mV <sub>pp</sub> @ full load	≤ 100 mV <sub>pp</sub> @ full load
Nominal output current @ U <sub>nom</sub>	5 A @ 55 °C	20 A @ 55 °C	10 A @ 55 °C
Continuous output current @ U <sub>nom</sub> (2.5 %/K derating above 55 °C)	5 A @ 55 °C, 3.125 A @ 70 °C	20 A @ 55 °C, 12.5 A @ 70 °C	10 A @ 55 °C, 6.25 A @ 70 °C
Output characteristic curve / current limit	Hiccup, I <sub>Limit</sub> : 110 - 130 %	Hiccup, I <sub>Limit</sub> : 110 - 130 %	Hiccup, I <sub>Limit</sub> : 110 - 130 %
Start-up period, max.	< 400 ms	< 300 ms	< 300 ms
Capacitive load	5500 µF	5500 µF	5500 µF
<b>Status Indicator/ Status Relay</b>			
DC OK: LED green , Relay: ON	> 0.9 U <sub>out</sub>	> 0.9 U <sub>out</sub>	> 0.9 U <sub>out</sub>
Max. contact switching power	30 V AC / DC, 1 A	30 V AC / DC, 1 A	30 V AC / DC, 1 A
Contact type	N. O. (SPST)	N. O. (SPST)	N. O. (SPST)
<b>Environmental Conditions</b>			
Ambient temperature, operational / storage, transport	-25...+70 °C / -40...+85 °C	-25...+70 °C / -40...+85 °C	-25...+70 °C / -40...+85 °C
Max. permitted humidity (operational)	5 %...95 % RH	5 %...95 % RH	5 %...95 % RH
<b>General Data</b>			
Power dissipation typ. @ 230 V AC, no-load / rated load	2 W / 19.2 W	2.0 W / 30.0 W	2.0 W / 30.0 W
Efficiency degree, typ. @ 230 V AC	95 %	95 %	95 %
Power factor, typ.	0.98 @ 120 V AC full load, 0.96 @ 230 V AC full load	0.99 @ 120 V AC full load, 0.96 @ 230 V AC full load	0.99 @ 120 V AC full load, 0.96 @ 230 V AC full load
Mains failure bridging @ I <sub>nom</sub>	>25ms @ 120 V AC, >25ms @ 230 V AC	> 20ms @ 120 V AC, > 20ms @ 230 V AC	> 20ms @ 120 V AC, > 20ms @ 230 V AC
Protection class	IP20	IP20	IP20
Protection class	I	I	I
Pollution degree	2	2	2
Insulation voltage, input-output	3.5 kV AC / 3.0 kV AC / 0.5 kV AC, 1 min.	3.5 kV AC / 3.0 kV AC / 0.5 kV AC, 1 min.	3.5 kV AC / 3.0 kV AC / 0.5 kV AC, 1 min.
Earth discharge current	< 3.5 mA	< 3.5 mA	< 3.5 mA
MTBF acc. to IEC 61709 (SN29500) @ 40°C	> 610000 h	> 540000 h	> 520000 h
Short-circuit protection	yes	yes	yes
Protection against inverse voltages from the load	< 60 V DC	< 35 V DC	< 60 V DC
Parallel capability	yes	yes	yes
Plastic housing	yes	yes	yes
Dimensions (Height x Width x Depth) in mm	130 x 52 x 100 mm	130 x 59 x 125 mm	130 x 59 x 125 mm
Weight	633 g	1368 g	1368 g
Approvals / Markings / Standards / Directives	CE, cULus, cCSAus	CE, cULus, cCSAus	CE, cULus, cCSAus
<b>Connection Data, Input / Output</b>			
Number of terminals, input / output/ N. O. relay (PUSH IN)	3 (L+, N-, PE) / 4 (+, +, -, -) / 2 (13,14)	3 (L+, N-, PE) / 4 (+, +, -, -) / 2 (13,14)	3 (L+, N-, PE) / 4 (+, +, -, -) / 2 (13,14)
Rigid wire cross-section	0.2 ...6 mm <sup>2</sup> / 0.2 ...6 mm <sup>2</sup> / 0.2 1.5 mm <sup>2</sup>	0.2 ...6 mm <sup>2</sup> / 0.2 ... 6 mm <sup>2</sup> / 0.2 1.5 mm <sup>2</sup>	0.2 ...6 mm <sup>2</sup> / 0.2 ... 6 mm <sup>2</sup> / 0.2 1.5 mm <sup>2</sup>
Flexible wire cross-section	0.5...2.5mm <sup>2</sup> / 0.5...2.5mm <sup>2</sup> / 0.2 0.75mm <sup>2</sup>	0.5 ...2.5mm <sup>2</sup> / 0.5 ...2.5mm <sup>2</sup> / 0.2 0.75mm <sup>2</sup>	0.5...2.5mm <sup>2</sup> / 0.5...2.5mm <sup>2</sup> / 0.2 0.75mm <sup>2</sup>
Wire cross-section AWG	26...12 / 26...12 / 28...14	26...10 / 26...10 / 28...14	26...10 / 26...10 / 28...14
Insulation stripping length	6 mm / 6 mm / 10 mm	6 mm / 6 mm / 10 mm	6 mm / 6 mm / 10 mm
Torque, min. / max.	0.5 Nm / 0.6 Nm	0.5 Nm / 0.6 Nm	0.5 Nm / 0.6 Nm
Screwdriver blade	0.6 x 3.5 mm	0.6 x 3.5 mm	0.6 x 3.5 mm
<b>EMC / shock / vibration</b>			
Interference radiation acc. to EN 55032 (Class)	B	B	B
Shock resistance (in all directions) acc. to IEC 60068-2-27 / Vibration resistance acc. to IEC 60068-2-6	30 g / 0.7 g	30 g / 0.7 g	30 g / 0.7 g
<b>Electrical Safety</b>			
Extra-low safety voltage according to	SELV: IEC 61010-1, PELV: IEC 61010-2-201		
Note: For AC operation, the max. permissible operating voltage must be observed in any case.			

## **Weidmuller – Your Solution Partner in Industrial Connectivity**

Be it automotive manufacturing, electricity generation or water management – there's hardly any industry that can do without electronics and electrical connectivity today. As experienced experts we support our customers and partners around the world with products, solutions and services in the industrial environment of power, signal and data. We are continuously developing innovative, sustainable and useful products and solutions for our customer's individual needs. We are a true partner with extensive knowledge and understanding of its customer and their application.

Together we set standards in Industrial Connectivity.

### **Weidmuller, Ltd**

10 Spy Court  
Markham, Ontario L3R 5H6  
Telephone: (800) 268-4080  
Facsimile: (877) 300-5635  
Email: [orders\\_can@weidmuller.com](mailto:orders_can@weidmuller.com)  
Website: [www.weidmuller.ca](http://www.weidmuller.ca)

### **Weidmuller, SA de CV**

Bldv. Hermanos Serdán 698,  
Col. San Rafael Oriente  
Puebla, Puebla, Mexico C.P. 72029  
Telephone: 01 222 2686267  
Facsimile: 01 222 2686219  
Email: [clientes@weidmuller.com](mailto:clientes@weidmuller.com)  
Website: [www.weidmuller.com.mx](http://www.weidmuller.com.mx)

### **Weidmuller, Inc**

821 Southlake Blvd.  
Richmond, Virginia 23236  
Telephone: (800) 849-9343  
Facsimile: (804) 379-2593  
Email: [info@weidmuller.com](mailto:info@weidmuller.com)  
Website: [www.weidmuller.com](http://www.weidmuller.com)

**Weidmüller** 